



## THE EUCLID CHEMICAL COMPANY

19218 REDWOOD ROAD • Cleveland, OH 44110  
(216) 531-9222 • (800) 321-7628 • FAX (216) 531-9596  
www.euclidchemical.com



# EUCO-FILL 50

## ANTI-WASHOUT ADMIXTURE

CONSTRUCTION PRODUCTS FOR

**VOX**

A SAFER ENVIRONMENT

**EUCO-FILL 50** is a liquid admixture designed to minimize the loss of cement and fine aggregates during the placement of backfill under water or when water is flowing through the placement area. It can also be used with cement-based grouts where water is a problem.

### PRIMARY APPLICATIONS

- Rockfill mixes
- Paste backfill mixes
- Grouting

### FEATURES/BENEFITS

- Minimizes washout of cement and fine aggregates

### PACKAGING

EUCO-FILL 50 is available in bulk, 275 gal (1041 liter) totes and 55 gal (208 liter) drums.

**Shelf Life:** 6 months in original, unopened container.

### DOSAGE

EUCO-FILL 50 is typically used at dosage rates of 6 oz to 75 oz / ton (400 to 4875 ml / tonne) of backfill for most applications. At higher dosage rates, set retardation is likely to occur.

### TECHNICAL INFORMATION

EUCO-FILL 50 can also be used at low dosages to reduce segregation in a mix.

### DIRECTIONS FOR USE

EUCO-FILL 50 is added to the mix after any other admixtures. If the consistency or slump of the mix is adjusted with water, it must be done before the addition of EUCO-FILL 50.

### PRECAUTIONS/LIMITATIONS

- Do not allow EUCO-FILL 50 to freeze
- Do not add water to the mix after the addition of EUCO-FILL 50
- Significant set retardation may occur with the use of this product.

### ADDITIONAL INFORMATION

For more information on the use of EUCO-FILL 50 or any other admixture, contact The Euclid Chemical Company, Underground Sales and Marketing at 1-800-321-7628, extension 8395. The Euclid Chemical Company will assist mining operations in testing of materials to assess correct admixture usage for specific applications.